

CAVO UL mercato americano

CAVO IN PVC RIGIDO UL STYLE 1569/1007



CARATTERISTICHE COSTRUTTIVE

Conduttore	Rigido
Isolante	PVC
Guaina	-
Tipo	Unipolare
Forma	Tondo
Isolamento	PVC

CONSTRUCTION FEATURES

Conductor	Solid
Insulating	PVC
Sheath	-
Type	Single-core
Shape	Round
Isolation	PVC

ACM SRL

CAVO UL mercato americano

CAVO IN PVC RIGIDO UL STYLE 1569/1007



CARATTERISTICHE TECNICHE

TECHNICAL FEATURES

Temperatura di utilizzo [°C]	-40°C÷80°C AWG 1007	Operating temperature [°C]	-40°C÷80°C AWG 1007
	-40°C÷105°C AWG 1569		-40°C÷105°C AWG 1569
Tensione nominale Uo/U	300 Vac	Test voltage	300 Vac
Raggio di curvatura	10XD	Bend radius	10XD

MARCHIO APPROVALS



NOMENCLATURA NOMENCLATURE

UL STYLE 1007/1569 SOLID

APPLICAZIONE

Cablaggi interni o usi in apparecchi elettronici non soggetti a sforzi meccanici

Idoneo per posa fissa

ACM SRL

Via Industriale 137/139 - Capriano del Colle (BS) 25020 - C.F. e P.IVA: 04401630985 - Tel: +39/030-9748379
e-mail: info@acm-lighting.com

Idoneo per posa interna

APPLICATION

Internal wiring or use in electronic equipment not subject to mechanical stress

Suitable for fixed installation

Suitable for indoor installation

COLORI COLORS



Altri colori su richiesta/ Other colors on request

MISURE MEASURES

Sezione Size conductor [mm ²]	Diametro esterno Outer diameter [mm]	Resistenza elettrica Electrical resistance [Ω/km]
AWG18	1.80 ± 0.10	6.6
AWG20	1.40 ± 0.10	10.5